

AMENDMENTS TO THE CLAIMS

Please cancel claims 3 and 16, and amend claims 1, 4-6, 10, 13 and 14. No new matter is believed to be introduced by the aforementioned amendments and new claims. The following listing of claims will replace all prior versions and listings of claims in the application.

1. **(Currently Amended)** An optoelectronic arrangement, comprising:
 - at least one emission component,
 - a monitor component, ~~which is~~ operatively coupled to the emission component and ~~detects at least some~~ detecting radiation radiated by the emission component,
 - a driver circuit electrically connected to the emission component and the monitor component, and
 - a carrier substrate,
 - the driver circuit being formed as a circuit integrated into the carrier substrate,
 - the monitor component likewise being integrated into the carrier substrate, and
 - the emission component being formed as a separate structural part and ~~being arranged on the carrier substrate~~ comprising a vertically emitting laser component which is fixed above the monitor component on the carrier substrate, part of the laser light being radiated upward and part of the laser light being radiated downward on to the monitor component, the laser component comprising a laser resonator and a laser substrate in which:
 - the laser resonator is arranged at a side of the laser component which is remote from the carrier substrate, and the laser substrate has, at a side facing the carrier substrate and in a manner adjoining the laser resonator, a cutout in such a way that downwardly radiated light falls on to the monitor component; or
 - the laser resonator is arranged at a side of the laser component which faces the carrier substrate, and the laser substrate has, at a side remote from the carrier substrate and in a manner adjoining the laser resonator, a cutout that facilitates radiating light away from the carrier substrate.
2. **(Previously Presented)** The arrangement according to Claim 1, the monitor component comprising a photodiode having a pn junction integrated into the carrier substrate.
3. **(Canceled)**

4. **(Currently Amended)** The arrangement according to Claim ~~[[3]]~~ 1,
 ~~the laser component comprising a laser substrate and a laser resonator,~~
 the laser resonator being arranged at a side of the laser component which is remote from
 the carrier substrate, and
 the laser substrate having, at a side facing the carrier substrate and in a manner adjoining
 the laser resonator, a cutout in such a way that downwardly radiated light falls on to the monitor
 component.
5. **(Currently Amended)** The arrangement according to Claim ~~[[3]]~~ 1,
 ~~the laser component comprising a laser substrate and a laser resonator,~~
 the laser resonator being arranged at a side of the laser component which faces the carrier
 substrate, and
 the laser substrate having, at a side remote from the carrier substrate and in a manner
 adjoining the laser resonator, a cutout that facilitates radiating light away from the carrier
 substrate.
6. **(Currently Amended)** The arrangement according to Claim 5, the laser component
 being arranged with a top side facing toward the carrier substrate and ~~in this case~~ having one or more
 electrical contacts located at the top side.
7. **(Previously Presented)** The arrangement according to Claim 1, the emission component
 being formed as a laser chip.
8. **(Previously Presented)** The arrangement according to Claim 1, the emission component
 being connected to the carrier substrate by at least one of adhesive bonding and wire bonding.
9. **(Previously Presented)** The arrangement according to Claim 1, the emission component
 being connected to the carrier substrate by flip-chip mounting.
10. **(Currently Amended)** The arrangement according to Claim ~~[[3]]~~ 1, further comprising
 an array of vertically emitting laser components and respectively assigned monitor components, wherein
 at least some of the laser light is radiated downward onto the associated monitor components.

11. **(Previously Presented)** The arrangement according to Claim 10,
 the array of vertically emitting laser components having a common laser substrate and
 respective laser resonators for the laser components,
 the respective laser resonators being arranged at respective sides of the laser components
 that face the carrier substrate, and
 respective laser substrates for the laser components having, at a side remote from the
 carrier substrate and in a manner adjoining the laser resonators, respective cutouts that facilitate
 radiating light away from the carrier substrate.
12. **(Previously Presented)** The arrangement according to Claim 10, the laser components
of the array being connected as redundant components.
13. **(Currently Amended)** The arrangement according to Claim ~~[[3]]~~ 1, the carrier substrate
being transparent to the radiated light.
14. **(Currently Amended)** The arrangement according to Claim ~~[[3]]~~ 1, the emission
component emitting light having a wavelength of between 650 and 850 nm.
15. **(Previously Presented)** The arrangement according to Claim 14, wherein the emission
component comprises GaAs.
16. **(Canceled)**
17. **(Previously Presented)** The arrangement according to Claim 1, wherein the driver
circuit is integrated monolithically into the carrier substrate.
18. **(Previously Presented)** The arrangement according to Claim 1, wherein the monitor
component is integrated monolithically into the carrier substrate.
19. **(Previously Presented)** The arrangement according to Claim 1, wherein the monitor
component comprises a diode.

20. **(Previously Presented)** The arrangement according to Claim 19, wherein the emission component comprises a laser chip, the diode being integrated monolithically into the carrier substrate and the laser chip being located on the carrier substrate above the diode.